

Data Safes

Access 1-Hour or 2-Hour Fire Resistant Data Safes

Security

Computer media is prone to accidental damage and it is recommended that storage temperature is below 125° and at a humidity level under 80%. Access data safes are available with either Underwriters Laboratories® Class 125 1-hour or 2-hour fire and impact ratings. In meeting the UL® standards, the internal temperature of Access data safes will not exceed 125°, while maintaining an interior relative humidity below 80% for either 1 or 2 hours when exposed to external temperatures up to 1,700°.

In addition, these data safes offer protection from dust, magnetic fields, unauthorized access, accidental damage and electrostatic discharge. A robust boltwork ensures that the safes' doors remain shut during building collapses or forced entry attempts.

Flexible Interiors

Access data safes can be equipped with a wide range of interior options. A variety of fixed shelves and composite drawers can accommodate any storage needs for sensitive magnetic media.

Full Composite Body

Access fire resistant data safes feature our proprietary barrier that delivers superior heat absorption, fire insulation and fire proofing in addition to a tough steel outer skin.



BDS-T670 Open



BDS-T670



BDS-T1000



BDS-T1000 Open

Locks

All data safes are furnished with UL listed high-security key locks with keys ready for use, while programmable electronic locks are available as options.

Features

- Programmable electronic lock for security and easy access
- Optional interiors allow various configurations to meet your storage needs

SPECIFICATIONS

Model #	Interior Dimensions (in.)			Exterior Dimensions (in.)			Interior	Weight
	Height	Width	Depth	Height	Width	Depth	Ft3	lb.
BDS-T370 - 1 hr. fire	4 3/4	10 1/2	8 1/4	14 1/4	19	15 3/4	0.24	140
BDS-T670 - 2 hr. fire	12 3/4	8 1/2	7	26	19 3/4	18 1/2	0.44	268
BDS-T1000 - 2 hr. fire	24 1/2	11 3/4	8 1/2	39	23 1/2	21	1.42	563
DS-1513-1LG	14 3/5	12 7/10	12 7/10	25 1/2	21 1/2	22 2/5	1.3	297
DS-1817-1LG	17 4/5	16 3/5	17	28 3/5	25 1/2	26 3/5	2.8	429
DS-2320-2	22 1/2	19 5/16	15 13/16	36 1/8	29 7/16	30	4.04	680
DS-3420-2	33 9/16	19 5/16	15 13/16	47 3/16	29 7/16	30	5.41	880
DS-4520-2	44 9/16	19 5/16	15 13/16	58 1/4	29 7/16	30	30	1070
DS-6420-2	63 1/8	19 5/16	15 13/16	76 13/16	29 7/16	30	10.78	1380
DS-6431-2	63 1/8	30 3/4	18 9/16	76 13/16	40 7/8	32 3/16	20.6	1870