

# Fire Safes

## Access 1-Hour and 2-Hour Fire Resistant Safes

### Security

Access fire resistant safes offer the ultimate in fire protection. They are available with either Underwriters Laboratories® Class 350 1-hour or 2-hour fire ratings. In meeting the UL® standards, the internal temperature of Access fire resistant safes will not exceed 350° for either 1 or 2 hours when exposed to external temperatures up to 1,700°.

### Features


- Vertical and horizontal bolts resist prying
- Bolt-O-Matic door guard automatically extends the 1" bolts when the door is closed
- Predrilled anchor point (most models)
- Light weight
- Electronic lock as standard



### SPECIFICATIONS

Model #	Interior Dimensions (in.)			Exterior Dimensions (in.)			Interior Ft3	Weight lb.
	Height	Width	Depth	Height	Width	Depth		
<b>1 HR. FIRE SAFES</b>								
BS-T310H	8	12 1/2	9 1/4	12 1/4	16 1/2	14	0.54	81
BS-T360H	9 1/4	15	12	14 1/4	19 1/4	16 3/4	0.96	125
<b>2 HR. FIRE SAFES</b>								
BS-C670 Drawer on top	18 1/2	14 1/4	12	24	19 3/4	18 1/2	1.83	231
BS-C1000 Drawer on bottom	30 1/2	17 1/2	14	37	23 3/4	21 1/4	4.32	462
BS-C1400 Drawer on bottom	45	20 3/4	18	54 1/2	27 1/2	25	9.73	737
BS-C1600 Drawer on bottom	53	24 3/4	18	62 1/2	31 1/2	25	13.66	935
BS-C1750 Double Door safe	57	38 3/4	18	67	45 1/4	25	23.01	1,650

Door Swing Dimensions (in)		
Model	A	B
BS-T310H	29.75	31.25
BS-T360H	35	36.25
BS-C670	37	37
BS-C1000	43.5	44.75
BS-C1400	51	52
BS-C1600	55	60
BS-C1750	46	87



All specifications are approximate and subject to change without notice.