

High Value Inventory Control Unit

All functions, including lock programming and operations, are centrally controlled by a single digital touch keypad with display screen. User access or exclusion can be precisely defined for each manager and user.

Drawers

Steel drawers, each with its own time delay lock are programmed from the Controller Keypad and can be programmed either collectively or individually.

Drawer-Specific Time Delay

Management can program any individual drawer or all drawers with a time delay from 1-99 seconds. Only 1 drawer opened at any time is the standard configuration but the unit can be programmed to have multiple drawers open at the same time.

Time Lock Interval

Management can program a time interval in which each or all drawers can be locked out to individual users.

Users

The unit accommodates up to 20 users. Each user will have a unique 8-digit PIN number. System can be programmed to allow or deny access to individual users for specific functions: access to all or some drawers; with or without time delay; and lock out with time lock.


Audit Feature

1,100 events can be read from the display screen. Optional computer download feature available.

Languages

User can select three languages for display screen readout: English, Spanish and French.

The UNIT CAN FUNCTION AS FREESTANDING OR FOR ADDED SECURITY, IT CAN BE INSERTED INTO A B-RATE, TL15, TL30 OR TRTL30X6 SAFE.



SPECIFICATIONS

Model	Drawer Size (in.)			Exterior Dimensions (in.)			Capacity	Weight
	Height	Width	Depth	Height	Width	Depth		
PG10	6	9 1/4	18	36 3/4	21	24 1/8	5.8	300
PG35	6	4	24	48 3/4	26 1/2	28 1/4	11.7	700
PG60	6	4	24	73	32	28 1/4	20	1400